







item No.	item name	photo	wattage		diameter (mm)	height (mm)	alu thickness	chips qty	chips type	chips power	initial power(W)	stable power(W) in 10 minutes	volt	Ra	flux(lm)	technology	color temperture	pcs/ctn	color box	ctn size
QSAL0105	A BULB-LINEAR-01		5w		50	90	0.52MM	5	2835	1W	4.8	4	220V	>70	240	linear	6500K/10000K	100	205 g	52*27*20
QSAL0107			7w		60	108	0.52MM	6	2835	1W	6.0	4.5	220V	>70	300	linear	6500K/10000K	100	205 g	62*32*23.5
QSAL0109			9w		60	108	0.52MM	10	2835	1W	8.2	5	220V	>70	410	linear	6500K/10000K	100	205 g	62*32*23.5
QSAL011201			12w		60	108	0.52MM	12	2835	1W	11.0	7.5	220V	>70	550	linear	6500K/10000K	100	205 g	62*32*23.5
QSAL011202			12w		65	116	0.52MM	12	2835	1W	11.0	7.5	220V	>70	550	linear	6500K/10000K	100	205 g	67*34.5*25.5
QSAL0115			15w		70	130	0.52MM	15	2835	1W	14.0	9	220V	>70	700	linear	6500K/10000K	100	205 g	70*36*27
QSAL0118			18w		80	142	0.52MM	18	2835	1W	16.5	13	220V	>70	825	linear	6500K/10000K	100	205 g	81*41.5*28.5
QSAL0125			25w		95	168	0.52MM	24	2835	1W	21	16	220V	>70	1050	linear	6500K/10000K	100	205 g	95*48.5*35


item No.	item name	photo	wattage		diameter (mm)	material	height (mm)	alu thickness (mm)	led chips	initial power(W)	stable power(W) in 10 minutes	volt	Ra	technology	pcs/ctn	color box	ctn size	G.W(KG)
QSAL0203	A BULB-220V-LINEAR-02		3w		45	pp+pp	78	0.7	6	2.7	2.2	220V	>70	linear	100	225g	26*26*32	2.28
QSAL0205			5w		55	pp+pp	90	0.7	7	3.4	2.8	220V	>70	linear	100	225g	28.5*28.5*36	2.95
QSAL0207			7w		60	pp+pp	106	0.7	8	3.49	3.1	220V	>70	linear	100	225g	32*32*41.5	3.93
QSAL0209			9w		70	pp+pp	120	0.7	9	3.6	4.1	220V	>70	linear	100	225g	35.5*35.5*46	4.95
QSAL0212			12w		80	pp+pp	130	0.7	10	4.4	4.3	220V	>70	linear	100	225g	41*41*50	5.82
QSAL0215			15w		85	pp+pp	143	0.7	12	5	5	220V	>70	linear	100	225g	44.5*44.5*54	6.85


item No.	item name	photo	wattage		diameter (mm)	height (mm)	alu thickness (mm)	led chips	chips type	chips power	initial power(W)	stable power(W) in 10 minutes	volt	Ra	flux(lm)	technology	color temperture	pcs/ctn	color box	ctn size
QSAL0305	A BULB-LINEAR-03-AC110V		5w		50	90	0.67	5	2835	36V-1W	4.8	4	110V	>70	288	linear	6500K	100	235g	52*26.5*19.5
QSAL0307			7w		60	110	0.67	6	2835	36V-1W	6.0	5	110V	>70	360	linear	6500K	100	235g	62*32*23.5
QSAL0309			9w		60	110	0.67	10	2835	36V-1W	8.2	5.5	110V	>70	492	linear	6500K	100	235g	62*32*23.5
QSAL031201			12w		60	110	0.67	12	2835	36V-1W	11.0	8.5	110V	>70	660	linear	6500K	100	235g	62*32*23.5
QSAL031202			12w		65	116	0.67	12	2835	36V-1W	11.0	8.5	110V	>70	660	linear	6500K	100	235g	70*36*27
QSAL0315			15w		70	132	0.67	15	2835	36V-1W	14.0	9.5	110V	>70	840	linear	6500K	100	235g	35.5*35.5*52
QSAL0318			18w		80	144	0.67	18	2835	36V-1W	16.5	13.8	110V	>70	990	linear	6500K	100	235g	81*41.5*28.5


item No.	item name	photo	wattage		diameter (mm)	material	height (mm)	alu thickness	chips qty	chips type	chips power	initial power (W)	stable power(W) in 10 minutes	volt	Ra	flux(lm)	technology	capacitor lifetime	capacitor	out current	color temperture	pcs/ctn	color box	ctn size	G.W(KG)
QSAD0105	A bulb-DOB		5w		50	PP aluminium+PC	90	0.63	4	2835	1.5w	4.8	4.4	165-245V	>70	312	DOB	6000H	2.2UF/400V	115MA	10000K	100	225g	52*27*20	3.3
QSAD0107			7w		60	PP aluminium+PC	108	0.63	6	2835	1.5w	6.5	6	165-245V	>70	423	DOB	6000H	2.2UF/400V	115MA	10000K	100	225g	62*32*23.5	5
QSAD0109			9w		60	PP aluminium+PC	108	0.63	8	2835	1.5w	8.5	7.4	165-245V	>70	553	DOB	6000H	3.3UF/400V	115MA	10000K	100	225g	62*32*23.5	5.1
QSAD011201			12w		60	PP aluminium+PC	108	0.63	9	2835	1.5w	11.0	8.5	165-245V	>70	715	DOB	6000H	3.3UF/400V	115MA	10000K	100	225g	62*32*23.5	5.1
QSAD011202			12w		65	PP aluminium+PC	116	0.63	9	2835	1.5w	11.0	8.5	165-245V	>70	715	DOB	6000H	3.3UF/400V	115MA	10000K	100	225g	67*34.5*25.5	5.4
QSAD0115			15w		70	PP aluminium+PC	130	0.63	12	2835	1.5w	14.0	9	165-245V	>70	910	DOB	6000H	4.7UF/400V	115MA	10000K	100	225g	70*36*27	6
QSAD0118			18w		80	PP aluminium+PC	140	0.63	16	2835	1.5w	17.0	14	165-245V	>70	1105	DOB	6000H	5.6UF/400V	115MA	10000K	100	225g	81*41.5*28.5	8
QSAD0125			25W		95	PP aluminium+PC	170	0.63	20	2835	1.5w	20.0	16	165-245V	>70	1300	DOB	6000H	6.8UF/400V	115MA	10000K	100	225g	95*48.5*35	10


item No.	item name	photo	wattage		diameter (mm)	material	height (mm)	alu thickness	chips qty	chips type	chips power	initial power (W)	stable power(W) in 10 minutes	volt	Ra	flux(lm)	technology	capacitor lifetime	capacitor	color temperture	pcs/ctn	color box	ctn size
QSAD0205	A bulb-DOB		5w		60	PA aluminium+PC	105	0.93	5	2835	1.0w	5.5	5	165-245V	>80	450	DOB	8000H	2.2UF/450V	6200K	100	225g	32*32*46
QSAD0207			7w		60	PA aluminium+PC	105	0.93	7	2835	1.0w	7.7	7	165-245V	>80	630	DOB	8000H	3.3UF/450V	6200K	100	225g	32*32*46
QSAD0209			9w		60	PA aluminium+PC	110	0.93	9	2835	1.0w	9.5	9	165-245V	>80	810	DOB	8000H	4.7UF/450V	6200K	100	225g	32*32*46
QSAD012201			12w		60	PA aluminium+PC	118	0.93	12	2835	1.0w	13.0	12	165-245V	>80	960	DOB	8000H	5.6UF/450V	6200K	100	225g	32*32*48
QSAD012202			12w		65	PA aluminium+PC	125	0.93	12	2835	1.0w	13.0	12	165-245V	>80	960	DOB	8000H	5.6UF/450V	6200K	100	225g	34.5*34.5*50
QSAD0215			15w		70	PA aluminium+PC	132	0.93	16	2835	1.0w	16.0	15	165-245V	>80	1350	DOB	8000H	6.8UF/450V	6200K	100	225g	37*37*52
QSAD0218			18w		80	PA aluminium+PC	143	0.93	21	2835	1.0w	18.5	18	165-245V	>80	1620	DOB	8000H	8.2UF/450V	6200K	100	225g	42*42*58
QSAD02220			20W		95	PA aluminium+PC	172	0.93	23	2835	1.0w	21.5	20	165-245V	>80	1800	DOB	8000H	8.2UF/450V	6200K	100	225g	48.5*48.5*35


item No.	item name	photo	wattage		diameter (mm)	material	height (mm)	chips qty	battery (mAh)	chips type	color temperture	initial power(W)	alu thickness (mm)	volt	Ra	flux(lm)	technology	capacitor	pcs/ctn	color box	ctn size	box size
QSAE0109	emergency bulb-DOB-01		9w		60	PP+PP	121	18D	1200	2835+2835	7500K 10000K	7	0.8	175-245V	70	450	DOB	3.3UF	100pcs	250g	32*32*51	6*6*12.2
QSAE0112			12W		70	PP+PP	134	22D	1200	2835+2835		9	0.8	175-245V	70	600	DOB	3.3UF	100pcs	250g	37*37*57	7*7*13.8
QSAE0115			15W		80	PP+PP	146	28D	1200	2835+2835		12W	0.8	175-245V	70	800	DOB	4.7uF	100pcs	250g	42*42*62	8*8*15


item No.	item name	photo	wattage		diameter (mm)	material	height (mm)	chips qty	battery (mAh)	chips type	color temperture	initial power(W)	stable power(W) in 10 minutes	alu thickness (mm)	volt	Ra	flux(lm)	technology	capacitor lifetime	capaciotr	out current	emergency current	pcs/ctn	color box	ctn size
QSAE0215	emergency bulb-2 batteries-DOB-02		15W		80	ABS+PP	175mm	28D	1200ma*2	5730+2835	10000K	13	11.5	1	175-265V	≥80	1077	DOB	6000H	4.7uf/400v	110ma	800-1000ma	100pcs	250g	42*42*66



item No.	item name	photo	wattage		diameter (mm)	material	height (mm)	chips qty	battery (mAh)	chips type	color temperture	initial power(W)	stable power(W) in 10 minutes	alu thickness (mm)	volt	Ra	flux(lm)	technology	capacitor lifetime	capaciotr	out current	emergency current	pcs/ctn	color box	ctn size
QSAE0315	emergency bulb-diamond-DOB-03		15W		80	PP+PC	158mm	27D	1200ma	5730+2835	10000K	13	10	1	175-265V	≥80	1077	DOB	6000H	4.7uf/400v	110ma	800-1000ma	100pcs	250g	42*42*66

item No.	item name	photo	wattage		diameter (mm)	material	height (mm)	alu thickness	chips type	initial power(W)	volt	Ra	flux(lm)	sensor distance	color temperture	pcs/ctn	ctn size
QSAS0105	sensor A bulb-linear		5w		60	pbt+pc	112	0.8	2835	4.9W	220-240V	70	400Lm	5-8M	6500	100	62*32*26
QSAS0107			7w		60	pbt+pc	118	0.8	2835	4.9W	220-240V	70	560Lm	5-8M	6500	100	62*32*26
QSAS0109			9w		65	pbt+pc	125	0.8	2835	8.7W	220-240V	70	720Lm	5-8M	6500	100	72*37*28
QSAS0112			12w		70	pbt+pc	132	0.8	2835	8.7W	220-240V	70	960Lm	5-8M	6500	100	72*37*28

item No.	item name	photo	wattage		diameter (mm)	material	height (mm)	alu thickness (mm)	led chips	chips type	chips power	initial power(W)	stable power(W) in 10 minutes	volt	Ra	flux(lm)	technology	color temperture	pcs/ctn	color box	ctn size	G.W(KG)	
QSACL0107	color A bulb-linear-01		7w		60	PP ALU+PC	108	0.52MM	6	2835	1W	5.8	6	220V	>70	316	LINEAR	6500K/10000K	100	225g	62*32*23	3.2	
QSACL0109			9w		60	PP ALU+PC	108	0.52MM	10	2835	1W	8.5	5.5	5.5	220V	>70	565	LINEAR	6500K/10000K	100	225g	62*32*23	3.2
QSACL0112			12w		60	PP ALU+PC	108	0.52MM	12	2835	1W	11.2	7.8	7.8	220V	>70	730	LINEAR	6500K/10000K	100	225g	62*32*23	3.2

item No.	item name	photo	wattage		diameter (mm)	material	height (mm)	alu thickness (mm)	chips qty	chips type	initial power(W)	stable power(W) in 10 minutes	volt	Ra	technology	pcs/ctn	color box	ctn size	N.W(kg)	G.W(kg)
QSGLO101	G45 color-01		1W		G45	ABS	68	0.63	4	2835	1.1	1.1	220V	>70	linear	200	200g	47*24*29	1.9	3.1

item No.	item name	photo	wattage		diameter (mm)	material	height (mm)	alu thickness (mm)	led chips	chips type	chips power	initial power(W)	stable power(W) in 10 minutes	volt	Ra	flux(lm)	technology	capacitor lifetime	capacitor	out current	color temperture	pcs/ctn	color box	ctn size	G.W(KG)
QSACD0107	color A bulb-DOB-01		7w		60	PP ALU+PC	108	0.63MM	4	3535	2W	6.7	6.2	165-245V	>70	470	DOB	6000H	2.2UF/400V	115MA	6500K	100	225g	62*32*23	3.3
QSACD0109			9w		60	PP ALU+PC	108	0.63MM	5	3535	2W	8.2	6.8	165-245V	>70	522	DOB	6000H	3.3UF/400V	115MA	6500K	100	225g	62*32*23	3.3
QSACD0112			12w		60	PP ALU+PC	108	0.63MM	7	3535	2W	11.8	8.9	165-245V	>70	770	DOB	6000H	3.3UF/400V	115MA	6500K	100	225g	62*32*23	3.3

item No.	item name	photo	wattage		diameter (mm)	material	height (mm)	alu thickness (mm)	chips qty	LED chips	chips power	initial power(W)	stable power(W) in 10 minutes	volt	Ra	flux(lm)	technology	capacitor lifetime	capacitor	out current	pcs/ctn	color box	ctn size	G.W(KG)
QSCD0105	C37-DOB-01		5W		C37	pbt+pc	98	0.8MM	7D	2835	6V1W	5W	4.4W	175-265V	>80	415	DOB	5000	3.3UF	110	100	250g	39*20.5*23	2.23KG
QSCD0107			7W		C37	pbt+pc	98	0.8MM	9D	2835	6V1W	7W	5.4W	175-265V	>80	589	DOB	5000	3.3UF	110	100	250g	39*20.5*23	2.29KG
QSCTD0105	C37T-DOB-01		5W		C37	pbt+pc	98	0.8MM	7D	2835	6V1W	5W	4.4W	175-265V	>80	415	DOB	5000	3.3UF	110	100	250g		
QSCTD0107			7W		C37	pbt+pc	98	0.8MM	9D	2835	6V1W	7W	5.4W	175-265V	>80	589	DOB	5000	3.3UF	110	100	250g		